Safety data sheet
according to UK REACH

Printing date 31.03.2026 *Version number 4.4 (replaces version 4.3)* *Revision: 31.03.2026*

*
SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Contacta Polystyrol-Kleber

Article number: 29602, 39602
1.2 Relevant identified uses of the substance or mixture and uses advised against
Sector of Use SU21 Consumer uses: Private households / general public / consumers
Application of the substance / the mixture Adhesives

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier:
Stanger Produktions- und Vertriebs GmbH
Ferdinand-Porsche-Straße 2
D-32339 Espelkamp
Telefon: +49 5743-9307-0

Hergestellt für:
Carrera Revell Europe GmbH
Henschelstr. 20-30
32257 Bünde / Germany
Telefon: +49 5223-965-0
www.revell.de

CARRERA REVELL OF AMERICAS INC.
Suite 307N
197 Route 18 South
East Brunswick, NJ 08816
Office: 609-409-8510
Email: office.americas@carrera-revell.com

Importeur:
ARWICO AG
Brühlstrasse 10
CH-4107 Ettingen
Switzerland

Further information obtainable from:
Product Safety Department
info@stanger.de

1.4 Emergency telephone number:
+49-5223- 965-0
(Monday to Friday, 7:00 - 17:00)
+49-5743-9307-0
(Monday to Friday, 7:00 a.m. - 5:00 p.m.)
Tox Info Suisse
24-h emergency number: 145 (from abroad: +41 44 251 51 51)
Information: +41 44 251 66 66

*
SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008
Flam. Liq. 3 H226 Flammable liquid and vapour.
STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
GHS label elements
The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet
according to UK REACH

Printing date 31.03.2026 *Version number 4.4 (replaces version 4.3)* *Revision: 31.03.2026*

Trade name: Contacta Polystyrol-Kleber

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07

Signal word *Warning*

Hazard-determining components of labelling:
n-butyl acetate
Hazard statements
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
Precautionary statements
P101 *If medical advice is needed, have product container or label at hand.*
P102 *Keep out of reach of children.*
P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
P261 *Avoid breathing dust/fume/gas/mist/vapours/spray.*
P303+P361+P353 *IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].*
P405 *Store locked up.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*
Additional information:
EUH066 Repeated exposure may cause skin dryness or cracking.
Labelling of packages where the contents do not exceed 125 ml
Hazard pictograms



GHS02 GHS07

Signal word *Warning*

Hazard-determining components of labelling:
n-butyl acetate
Hazard statements
H336 May cause drowsiness or dizziness.
Precautionary statements
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P405 Store locked up.
2.3 Other hazards
Results of PBT and vPvB assessment *Not applicable*
PBT: *Not applicable*
vPvB: *Not applicable*

*
SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: *Mixture of substances listed below with nonhazardous additions.*

Dangerous components:		
CAS: 123-86-4 *EINECS: 204-658-1* *Reg.nr.: 01-2119485493-29*	*n-butyl acetate* *Flam. Liq. 3, H226; STOT SE 3, H336, EUH066*	*25-75%*

(Contd. on page 3)

Safety data sheet
according to UK REACH

Trade name: Contacta Polystyrol-Kleber

(Contd. of page 2)

Additional information: *For the wording of the listed hazard phrases refer to section 16.*

*
SECTION 4: First aid measures

4.1 Description of first aid measures
General information: *Immediately remove any clothing soiled by the product.*
After inhalation: *Supply fresh air; consult doctor in case of complaints.*
After skin contact: *Immediately wash with water and soap and rinse thoroughly.*
After eye contact: *Rinse opened eye for several minutes under running water.*
After swallowing: *Call for a doctor immediately, present msds*
4.2 Most important symptoms and effects, both acute and delayed *No further relevant information available.*
4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

*
SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents:
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
For safety reasons unsuitable extinguishing agents: *Water with full jet*
5.2 Special hazards arising from the substance or mixture *No further relevant information available.*
5.3 Advice for firefighters
Protective equipment: *Wear self-contained respiratory protective device.*

*
SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: *Do not allow to enter sewers/ surface or ground water.*
6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
No special measures required.
6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*
SECTION 7: Handling and storage

7.1 Precautions for safe handling *Prevent formation of aerosols.*
Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles:
Protect from frost and heat. Optimal storage temperature 10 - 25 °C
Information about storage in one common storage facility: *Not required*
Further information about storage conditions: *Keep container tightly sealed.*
Storage class: *3*

(Contd. on page 4)

Safety data sheet
according to UK REACH

(Contd. of page 3)

7.3 Specific end use(s) *No further relevant information available.*

*
SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
123-86-4 n-butyl acetate	
WEL	*Short-term value: 966 mg/m³, 200 ppm* *Long-term value: 724 mg/m³, 150 ppm*

Additional information: *The lists valid during the making were used as basis.*

8.2 Exposure controls
Appropriate engineering controls *No further data; see section 7.*
Individual protection measures, such as personal protective equipment
General protective and hygienic measures:
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Respiratory protection: *Not required*
Hand protection
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:
Butyl rubber, BR
Nitrile rubber, NBR
For the permanent contact gloves made of the following materials are suitable: *Butyl rubber, BR*
For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Nitrile rubber, NBR
Chloroprene rubber, CR
Eye/face protection *Tightly sealed goggles*

*
SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information

Physical state	*Liquid*
Colour:	*Colourless*
Odour:	*Solvent-like*
Boiling point or initial boiling point and boiling range	*Undetermined*
Lower and upper explosion limit	
Lower:	*1.1 Vol %*
Upper:	*8 Vol %*

(Contd. on page 5)

Safety data sheet
according to UK REACH

Trade name: Contacta Polystyrol-Kleber

(Contd. of page 4)

Flash point:	26 °C
Auto-ignition temperature:	370 °C
pH	Mixture is non-polar/aprotic.
Viscosity:	
Dynamic at 20 °C:	3,500 mPas
Solubility	
water:	Not miscible or difficult to mix.
Vapour pressure at 20 °C:	13 hPa
Density and/or relative density	
Density at 20 °C:	0.93 g/cm³
9.2 Other information	No further relevant information available.
Appearance:	
Form:	Viscous
Important information on protection of health and environment, and on safety.	
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent separation test:	
Organic solvents:	65.0 %
VOC (EC)	604.5 g/l 65.00 %
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

*
SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.
10.2 Chemical stability
Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
10.3 Possibility of hazardous reactions No dangerous reactions known.
10.4 Conditions to avoid No further relevant information available.
10.5 Incompatible materials: No further relevant information available.
10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

Safety data sheet
according to UK REACH

Trade name: Contacta Polystyrol-Kleber

(Contd. of page 5)

*
SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
123-86-4 n-butyl acetate		
Oral	LD50	>4,700 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

STOT-single exposure May cause drowsiness or dizziness.
11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

*
SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity: No further relevant information available.
12.2 Persistence and degradability No further relevant information available.
12.3 Bioaccumulative potential No further relevant information available.
12.4 Mobility in soil No further relevant information available.
12.5 Results of PBT and vPvB assessment Not applicable
12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
12.7 Other adverse effects No further relevant information available.
Additional ecological information:
General notes:
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

*
SECTION 13: Disposal considerations

13.1 Waste treatment methods
Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

*
SECTION 14: Transport information

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1133
14.2 UN proper shipping name	
ADR	UN1133 ADHESIVES
IMDG, IATA	ADHESIVES

(Contd. on page 7)

Safety data sheet
according to UK REACH

Trade name: Contacta Polystyrol-Kleber

(Contd. of page 6)

14.3 Transport hazard class(es)

ADR



Class	3 (F1) Flammable liquids.
Label	3

IMDG, IATA



Class	3 Flammable liquids.
Label	3

14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-D
14.7 Maritime transport in bulk according to IMO instruments	Not applicable

Transport/Additional information:

ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

*
SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

(Contd. on page 8)

Safety data sheet
according to UK REACH

Trade name: Contacta Polystyrol-Kleber

(Contd. of page 7)

Reportable explosives precursors
None of the ingredients is listed.

Reportable poisons
None of the ingredients is listed.

Directive 2012/18/EU
Named dangerous substances - ANNEX I None of the ingredients is listed.
Seveso category P5c FLAMMABLE LIQUIDS
Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*
SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing SDS: Product Safety Department
Contact: Stanger Produktion und Vertrieb GmbH
Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
*** Data compared to the previous version altered.**