Safety data sheet
according to UK REACH

Printing date 31.03.2026 *Version number 1.3 (replaces version 1.2)* *Revision: 31.03.2026*

*
SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Revell Color Mix

Article number: 39611, 39612, 29611

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU21 Consumer uses: Private households / general public / consumers

Application of the substance / the mixture Thinner, Diluent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Stanger Produktions- und Vertriebs GmbH
Ferdinand-Porsche-Straße 2
D-32339 Espelkamp
Telefon: +49 5743-9307-0

Hergestellt für:
Carrera Revell Europe GmbH
Henschelstr. 20-30
32257 Bünde / Germany
Telefon: +49 5223-965-0
www.revell.de

CARRERA REVELL OF AMERICAS INC.
Suite 307N
197 Route 18 South
East Brunswick, NJ 08816
Office: 609-409-8510
Email: office.americas@carrera-revell.com

Importeur:
ARWICO AG
Brühlstrasse 10
CH-4107 Ettingen
Switzerland

Further information obtainable from:

Product Safety Department
info@stanger.de

1.4 Emergency telephone number:

+49-5743-9307-0
(Monday to Friday, 7:00 a.m. - 5:00 p.m.)
+49-5223- 965-0
(Monday to Friday, 7:00 - 17:00)
Tox Info Suisse
24-h emergency number: 145 (from abroad: +41 44 251 51 51)
Information: +41 44 251 66 66

*
SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet
according to UK REACH

Trade name: Revell Color Mix

(Contd. of page 1)

GHS label elements
The product is classified and labelled according to the GB CLP regulation.
Hazard pictograms



GHS02 GHS07 GHS08

Signal word *Danger*

Hazard-determining components of labelling:
Naphtha (petroleum), hydrotreated heavy
propan-2-ol
Hazard statements
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
Precautionary statements

P101	*If medical advice is needed, have product container or label at hand.*
P102	*Keep out of reach of children.*
P210	*Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
P261	*Avoid breathing dust/fume/gas/mist/vapours/spray.*
P280	*Wear eye protection / face protection.*
P301+P310	*IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*
P331	*Do NOT induce vomiting.*
P304+P340	*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
P305+P351+P338	*IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P405	*Store locked up.*
P501	*Dispose of contents/container in accordance with local/regional/national/international regulations.*

Labelling of packages where the contents do not exceed 125 ml
Hazard pictograms



GHS02 GHS07 GHS08

Signal word *Danger*

Hazard-determining components of labelling:
Naphtha (petroleum), hydrotreated heavy
propan-2-ol
Hazard statements
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
Precautionary statements

P101	*If medical advice is needed, have product container or label at hand.*
P102	*Keep out of reach of children.*
P261	*Avoid breathing dust/fume/gas/mist/vapours/spray.*
P301+P310	*IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*
P331	*Do NOT induce vomiting.*
P304+P340	*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
P405	*Store locked up.*
P501	*Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

Safety data sheet
according to UK REACH

Printing date 31.03.2026 *Version number 1.3 (replaces version 1.2)* *Revision: 31.03.2026*

Trade name: Revell Color Mix

(Contd. of page 2)

2.3 Other hazards
Results of PBT and vPvB assessment Not applicable
PBT: Not applicable
vPvB: Not applicable

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-75%
CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33 01-2119486659-16	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	25-75%

Additional information:
Benzene content less than 0.1%. Classification as a carcinogen is not applicable (Note P of the EC - List of substances / Annex VI of EC Regulation 1272/2008).
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Immediately wash with water and soap and rinse thoroughly.
After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Call for a doctor immediately, present msds
4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents:
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
For safety reasons unsuitable extinguishing agents: Water with full jet
5.2 Special hazards arising from the substance or mixture No further relevant information available.
5.3 Advice for firefighters
Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
No special measures required.

(Contd. on page 4)

Safety data sheet
according to UK REACH

(Contd. of page 3)

6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Prevent formation of aerosols.
Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: Store in a cool location.
Information about storage in one common storage facility: Not required
Further information about storage conditions:
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Storage class: 3
7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
67-63-0 propan-2-ol	
WEL	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

DNELs	
64742-48-9 Naphtha (petroleum), hydrotreated heavy	
DNEL	1,500 mg/m³ (Worker) 900 mg/m³ (Consumer)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls
Appropriate engineering controls No further data; see section 7.
Individual protection measures, such as personal protective equipment
General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Respiratory protection: Not required
Hand protection
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet
according to UK REACH

(Contd. of page 4)

Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:
Nitrile rubber, NBR
For the permanent contact gloves made of the following materials are suitable: *Butyl rubber, BR*
For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Nitrile rubber, NBR
Chloroprene rubber, CR
Eye/face protection *Tightly sealed goggles*

*
SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information	
Physical state	*Liquid*
Colour:	*According to product specification*
Odour:	*Mild*
Boiling point or initial boiling point and boiling range	*82 °C*
Lower and upper explosion limit	
Lower:	*0.6 Vol %*
Upper:	*12 Vol %*
Flash point:	*12 °C*
Auto-ignition temperature:	*240 °C*
pH	*Mixture is non-polar/aprotic.*
Viscosity:	
Kinematic viscosity at 20 °C	*12 s (DIN 53211/4)*
Solubility	
water:	*Not miscible or difficult to mix.*
Vapour pressure at 20 °C:	*4 hPa*
Density and/or relative density	
Density at 20 °C:	*0.7 g/cm³*

9.2 Other information	*No further relevant information available.*
Appearance:	
Form:	*Not determined*
Important information on protection of health and environment, and on safety.	
Explosive properties:	*Product is not explosive. However, formation of explosive air/vapour mixtures are possible.*
Solvent separation test:	
Organic solvents:	*100.0 %*
VOC (EC)	*700.0 g/l*
	100.00 %

Information with regard to physical hazard classes	
Explosives	*Void*
Flammable gases	*Void*
Aerosols	*Void*
Oxidising gases	*Void*
Gases under pressure	*Void*
Flammable liquids	*Highly flammable liquid and vapour.*
Flammable solids	*Void*
Self-reactive substances and mixtures	*Void*
Pyrophoric liquids	*Void*

(Contd. on page 6)

Safety data sheet
according to UK REACH

(Contd. of page 5)

Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.
10.2 Chemical stability
Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
10.3 Possibility of hazardous reactions No dangerous reactions known.
10.4 Conditions to avoid No further relevant information available.
10.5 Incompatible materials: No further relevant information available.
10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
67-63-0 propan-2-ol		
Oral	LD50	4,570 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	8,000 mg/kg (rat)
Dermal	LD50	4,000 mg/kg (rat)
Inhalative	LC50/4 h	>18.5 mg/l (rat)

Primary irritant effect:
Serious eye damage/irritation Causes serious eye irritation.
STOT-single exposure May cause drowsiness or dizziness.
Aspiration hazard May be fatal if swallowed and enters airways.
11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity: No further relevant information available.
12.2 Persistence and degradability No further relevant information available.
12.3 Bioaccumulative potential No further relevant information available.
12.4 Mobility in soil No further relevant information available.
12.5 Results of PBT and vPvB assessment Not applicable
12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
12.7 Other adverse effects No further relevant information available.

(Contd. on page 7)

Safety data sheet
according to UK REACH

Trade name: Revell Color Mix

(Contd. of page 6)

Additional ecological information:
General notes:
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

*
SECTION 13: Disposal considerations

13.1 Waste treatment methods
Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:
Recommendation: *Disposal must be made according to official regulations.*

SECTION 14: Transport information

14.1 UN number or ID number	
ADR, IMDG, IATA	*UN1263*
14.2 UN proper shipping name	
ADR	*UN1263 PAINT*
IMDG, IATA	*PAINT*
14.3 Transport hazard class(es)	
ADR	



Class	*3 (F1) Flammable liquids.*
Label	*3*
IMDG, IATA	



Class	*3 Flammable liquids.*
Label	*3*
14.4 Packing group	
ADR, IMDG, IATA	*II*
14.5 Environmental hazards:	*Not applicable*
14.6 Special precautions for user	*Warning: Flammable liquids.*
Hazard identification number (Kemler code):	*33*
EMS Number:	*F-E,S-E*
Stowage Category	*B*
14.7 Maritime transport in bulk according to IMO instruments	*Not applicable*

(Contd. on page 8)

Safety data sheet
according to UK REACH

Trade name: Revell Color Mix

(Contd. of page 7)

Transport/Additional information:

ADR

Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E

IMDG

Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Poisons Act

Regulated explosives precursors
None of the ingredients is listed.

Regulated poisons
None of the ingredients is listed.

Reportable explosives precursors
None of the ingredients is listed.

Reportable poisons
None of the ingredients is listed.

Directive 2012/18/EU
Named dangerous substances - ANNEX I None of the ingredients is listed.
Seveso category P5c FLAMMABLE LIQUIDS
Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*
SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing SDS: Product Safety Department
Contact: Stanger Produktion und Vertrieb GmbH
Abbreviations and acronyms:
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)

Safety data sheet
according to UK REACH

Printing date 31.03.2026 *Version number 1.3 (replaces version 1.2)* *Revision: 31.03.2026*

Trade name: Revell Color Mix

(Contd. of page 8)

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
**** Data compared to the previous version altered.***