Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

*
1 Identification

· **Product identifier**

· **Trade name: REVELL-SPRAY-COLOR**
Different shades and gloss levels / metallic finishers

· **Article number:**
Dreisol:
matt:
R3600-0102; R3600-1115; R3600-1116; R3600-1188; R3600-2125; R3600-3136; R3600-5156; R3600-6146; R3600-7109; R3600-7157; R3600-7176; R3600-7178; R3600-8185; R3600-9105; R3600-9108; R3600-9190; R3600-9191; R3600-9194; R3600-9199

seidenmatt:
R3620-3330; R3620-7371; R3620-7374; R3620-9301; R3620-9302

glänzend:
R3680-0101; R3680-1112; R3680-3131; R3680-3134; R3680-5152; R3680-5200; R3680-9104; R3680-9107; R3680-0100

Revell:
matt:
34102; 34115; 34116; 34188; 34125; 34136; 34156; 34146; 34109; 34157; 34176; 34178; 34185; 34105; 34108; 34190; 34191; 34194; 34199

seidenmatt:
34330; 34371; 34374; 34301; 34302

glänzend:
34101; 34112; 34131; 34134; 34152; 34200; 34104; 34107; 39627

· **Application of the substance / the mixture** Coating material for model making

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Dreisol Coatings GmbH & Co.KG. Tel.: +49(0)5742-9300-0(Zentrale)
Industriestraße 4 Fax : +49(0)5742-9300-49
D-32361 Pr. Oldendorf-Bad Holzhausen E-Mail: mail@dreisol.de
http://www.dreisol.de

Carrera Revell Europe GmbH
Henschelstr. 20-30 Tel.: +49(0)5223-965-0
D-32257 Bünde http://www.revell.de
Carrera Revell of Americas Inc.
Suite 307N
197 Route 18 South Office: 609-409-8510
East Brunswick, NJ 08816, USA http://www.carrera-revell-toys.com

· **Information department:**
Product Safety Department Tel.: +49(0)5742-9300-41
E-mail address of the competent person: sdb@dreisol.de

*
2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

Aerosols 1 H222 Extremely flammable aerosol.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 *Reviewed on 07/01/2026*

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 1)



GHS08 Health hazard

Carcinogenicity 2 *H351 Suspected of causing cancer.*



GHS07

Eye Irritation 2A *H319 Causes serious eye irritation.*

Sensitization - Skin 1 *H317 May cause an allergic skin reaction.*

· **Additional information:**
A marking with aspiration GHS 08 and H304 is in accordance with Regulation (EC) No 1272/2008 Annex I Nr.1.3.3. not necessary (aerosol packaging)

· **Label elements**
· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**
ethylbenzene
methyl methacrylate
butyl methacrylate
· **Hazard statements**
Extremely flammable aerosol.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 2)

Wash contaminated clothing before reuse.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**
· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 4
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 4
Reactivity = 3

*
3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Dangerous components:**		
115-10-6	dimethyl ether	50-100%
	Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic compounds (outside EU: CAS 64742-49-0))	12.5-20%
110-12-3	5-methylhexan-2-one	7-10%
	Hydrocarbobns C9 aromatics (outside EU: CAS64742-95-6)*	7-10%
64-17-5	ethanol	3-5%
100-41-4	ethylbenzene	0.1-0.2%

· **Additional information:**
*) Benzene content is less than 0.1% (EINECS-No. 200-753-7). It is P. Note
Contains no other ingredients (≥0,1%) that are classified as hazardous to health or the environment according to the current knowledge of the supplier and must be mentioned in this section.

4 First-aid measures

· **Description of first aid measures**
· **General information:** Immediately remove any clothing soiled by the product.
· **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:** Do not induce vomiting; immediately call for medical help.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 3)

*
5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:**
recommended: foam (if necessary alcohol resistant), carbon dioxide, extinguishing powder
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **Special hazards arising from the substance or mixture**
Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazards.
· **Advice for firefighters**
· **Protective equipment:** Wear self-contained respiratory protective device.
· **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

*
6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Remove all sources of ignition. Provide adequate ventilation. Refer to protective measurer, listed in sections 7 and 8.
· **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
· **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
115-10-6	dimethyl ether	500 ppm
110-12-3	5-methylhexan-2-one	50 ppm
64-17-5	ethanol	1800 ppm
1330-20-7	xylene, mixed isomers, pure	130 ppm
112945-52-5	Siliciumdioxid SiO2	18 mg/m3
100-41-4	ethylbenzene	33 ppm
1309-37-1	diiron trioxide	15 mg/m3
64742-48-9	Naphtha (petroleum), hydrotreated heavy	600 mg/m3
7631-86-9	silicon dioxide, chemically prepared	18 mg/m3
110-82-7	cyclohexane	800 ppm
80-62-6	methyl methacrylate	17 ppm
97-88-1	butyl methacrylate	30 ppm
1333-86-4	Carbon black	9 mg/m3
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
123-86-4	n-butyl acetate	5.0 ppm
122-99-6	2-phenoxyethanol	5.7 mg/m3

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 4)

108-88-3	toluene	67 ppm
98-82-8	Cumol	50 ppm
556-67-2	octamethylcyclotetrasiloxane	360 ppm

· **PAC-2:**

115-10-6	dimethyl ether	1200 ppm
110-12-3	5-methylhexan-2-one	550 ppm
64-17-5	ethanol	3300 ppm
1330-20-7	xylene, mixed isomers, pure	920 ppm
112945-52-5	Siliciumdioxid SiO2	100 mg/m3
100-41-4	ethylbenzene	1100 ppm
1309-37-1	diiron trioxide	360 mg/m3
64742-48-9	Naphtha (petroleum), hydrotreated heavy	6600 mg/m3
7631-86-9	silicon dioxide, chemically prepared	500 mg/m3
110-82-7	cyclohexane	1700 ppm
80-62-6	methyl methacrylate	120 ppm
97-88-1	butyl methacrylate	36 ppm
1333-86-4	Carbon black	290 mg/m3
108-65-6	2-methoxy-1-methylethyl acetate	1000 ppm
123-86-4	n-butyl acetate	200 ppm
122-99-6	2-phenoxyethanol	42 mg/m3
108-88-3	toluene	560 ppm
98-82-8	Cumol	300 ppm
556-67-2	octamethylcyclotetrasiloxane	530 ppm

· **PAC-3:**

115-10-6	dimethyl ether	7200 ppm
110-12-3	5-methylhexan-2-one	3300 ppm
64-17-5	ethanol	15000 ppm
1330-20-7	xylene, mixed isomers, pure	2500 ppm
112945-52-5	Siliciumdioxid SiO2	630 mg/m3
100-41-4	ethylbenzene	1800 ppm
1309-37-1	diiron trioxide	2200 mg/m3
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40000 mg/m3
7631-86-9	silicon dioxide, chemically prepared	3000 mg/m3
110-82-7	cyclohexane	10000 ppm
80-62-6	methyl methacrylate	570 ppm
97-88-1	butyl methacrylate	220 ppm
1333-86-4	Carbon black	1750 mg/m3
108-65-6	2-methoxy-1-methylethyl acetate	5000 ppm
123-86-4	n-butyl acetate	3000 ppm
122-99-6	2-phenoxyethanol	250 mg/m3
108-88-3	toluene	3700 ppm
98-82-8	Cumol	730 ppm

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 5)

556-67-2	octamethylcyclotetrasiloxane	1600 ppm

*
7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Keep receptacles tightly sealed.
Avoid contact with skin and eyes.
· **Information about protection against explosions and fires:**
Protect against electrostatic charges.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Vapours are heavier than air and may spread along floors. Vapours may from explosive mixture with air.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Information about storage in one common storage facility:**
Keep away from foodstuffs, beverages and food.
· **Further information about storage conditions:** Protect from heat and direct sunlight.
· **Storage class:** 2 B
· **Specific end use(s)** No further relevant information available.

*
8 Exposure controls/personal protection

· **Additional information about design of technical systems:**
Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

115-10-6 dimethyl ether	
WEEL	Long-term value: 1000 ppm
110-12-3 5-methylhexan-2-one	
PEL	Long-term value: 475 mg/m³, 100 ppm
REL	Long-term value: 240 mg/m³, 50 ppm
TLV	Short-term value: 233 mg/m³, 50 ppm Long-term value: 93 mg/m³, 20 ppm
64-17-5 ethanol	
PEL	Long-term value: 1900 mg/m³, 1000 ppm
REL	Long-term value: 1900 mg/m³, 1000 ppm
TLV	Short-term value: 1880 mg/m³, 1000 ppm A3

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 6)

100-41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

· **Ingredients with biological limit values:**

100-41-4 ethylbenzene	
BEI	0.15 g/g creatinine Medium: urine Time: end of shift Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing.
· **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Filter A/P2
· **Protection of hands:**
The instructions and information provided by the glove manfacturer on use, storage, maintenance and replacement must be followed. Barrier creams may help to protect the exposed areas of the skin.
· **Material of gloves**
Gloves made of nitrile rubber or butyl rubber (0.4mm). Breakthrough time > 480min with full contact. Observe the glove manufacturer's specifications on permeability and breakthrough times and the special conditions at the workplace. In case of cracking or change of color, shape or elasticity the gloves have to be changed immediately.
· **Eye protection:** Tightly sealed goggles
· **Body protection:** Protective work clothing

*
9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Aerosol
Color:	According to product specification
· **Odor:**	Characteristic
· **Odor threshold:**	Not determined
· **pH-value:**	Not determined
· **Boiling point/Boiling range:**	-24 °C (-11.2 °F)
· **Flash point:**	-42 °C (-43.6 °F) (DIN/ISO 3679)
· **Flammability:**	Not applicable

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 7)

· **Auto igniting:**	235 °C (455 °F) (DIN 51794)
· **Decomposition temperature:**	Not determined
· **Danger of explosion:**	Not determined
· **Explosion limits:**	
Lower:	0.1 Vol %
Upper:	27.7 Vol %
· **Vapor pressure at 20 °C (68 °F):**	5,200 hPa (3.900 mm Hg)
· **Density at 20 °C (68 °F):**	0.82 g/cm³ (6.8429 lbs/gal) (DIN/ISO 2811)
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not applicable.
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not determined
Kinematic:	Not determined
· **Solvent content:**	
Organic solvents:	90 %
VOC content:	90.65 %
VOC (EG)	740.9 g/l
Solids content:	10 %
· **Other information**	No further relevant information available.

*
10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
Stable under recommended storage and handling conditions (see section 7).
Hazardous products of decomposition could result at high temperatures.
· **Possibility of hazardous reactions**
In case of completly combustion tocix gases are developed including carbon monoxide.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.

*
11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**
There are no data available on the preparation itself.
The mixture is classified under Regulation No 1272/2008 = CLP (EU-GHS) Regulation and the toxicological hazards. See Section 3 and 15 for details.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 *Reviewed on 07/01/2026*

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 8)

· **LD/LC50 values that are relevant for classification:**

115-10-6 dimethyl ether		
Inhalative	LC50/4 h	308 mg/l (rat (Ratte))
Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic compounds (outside EU:CAS 64742-49-0))		
Oral	LD50	5,000 mg/kg (rat (Ratte))
Dermal	LD50	3,000 mg/kg (rab)
110-12-3 5-methylhexan-2-one		
Oral	LD50	5,657 mg/kg (rat (Ratte))
Hydrocarbobns C9 aromatics (outside EU: CAS64742-95-6)*		
Oral	LD50	>2,000 mg/kg (rat (Ratte))
Dermal	LD50	>2,000 mg/kg (rab)
Inhalative	LC50/4 h	>5 mg/l (rat (Ratte))
64-17-5 ethanol		
Oral	LD50	10,470 mg/kg (rat (Ratte))
Dermal	LD50	>2,000 mg/kg (rab)
Inhalative	LC50/4 h	117-125 mg/l (rat (Ratte))
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat (Ratte))
Dermal	LD50	15,500 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (rat (Ratte))

· **Primary irritant effect:**
· **on the skin:** No irritant effect.
· **on the eye:** No irritating effect.
· **Sensitization:** No sensitizing effects known.
· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
64-17-5	ethanol	1
1330-20-7	xylene, mixed isomers, pure	3
100-41-4	ethylbenzene	2B
1309-37-1	diiron trioxide	3
7631-86-9	silicon dioxide, chemically prepared	3
80-62-6	methyl methacrylate	3
97-88-1	butyl methacrylate	2B
1333-86-4	Carbon black	2B
108-88-3	toluene	3
98-82-8	Cumol	2B

· **NTP (National Toxicology Program)**		
98-82-8	Cumol	R

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 9)

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

*
12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**	
110-12-3 5-methylhexan-2-one	
LC50/96h	159 mg/l (fish)
EC50/72h	>100 mg/l (algae)
Hydrocarbobns C9 aromatics (outside EU: CAS64742-95-6)*	
LC/EC/IC50	> 1-≤10 mg/l (algae) > 1-≤10 mg/l (fish) > 1-≤10 mg/l (invertebrates (Wirbellose))
100-41-4 ethylbenzene	
LC50/96h	4.2 mg/l (Onchorhynchus mykiss (Regenbogenforelle))
EC50/48h	1.8-2.9 mg/l (daphnia magnia (Wasserfloh))
EC50/72h	4.6 mg/l (algae)

· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Ecotoxical effects:**
· **Remark:** Harmful to fish
· **Other information:** There are no data available on the preparation itself.
· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
· **Other adverse effects** No further relevant information available.

*
13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
The relevant EU directives as well as local, regional and national regulations must be observed. Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**
· **Recommendation:**
Disposal must be made according to official regulations.

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 10)

Emptied containers must be sent for scrap recycling or reconditioning. Containers that have not been emptied properly are hazardous waste (waste code no. 150110).

*

14 Transport information

· **UN-Number**	
· **DOT, ADR, IMDG, IATA**	UN1950
· **UN proper shipping name**	
· **DOT**	Aerosols, flammable
· **ADR, IMDG**	AEROSOLS
· **IATA**	AEROSOLS, flammable
· **Transport hazard class(es)**	
· **Class**	2.1 Gases
· **Label**	2.1
· **ADR**	



· **Class**	2 5F Gases
· **Label**	2.1
· **IMDG, IATA**	



· **Class**	2.1 Gases
· **Label**	2.1
· **Packing group**	
· **DOT, ADR, IMDG, IATA**	not regulated
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Warning: Gases
· **Hazard identification number (Kemler code):**	-
· **EMS Number:**	F-D,S-U
· **Stowage Code**	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **DOT**	
· **Quantity limitations**	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 11)

· **ADR**	
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **UN "Model Regulation":**	UN 1950 AEROSOLS, 2.1

*
15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **TSCA (Toxic Substances Control Act):**

· **Hazardous Air Pollutants**	
1330-20-7	xylene, mixed isomers, pure
100-41-4	ethylbenzene
80-62-6	methyl methacrylate
122-99-6	2-phenoxyethanol
108-88-3	toluene
98-82-8	Cumol

· **Proposition 65**
· **Chemicals known to cause cancer:**
For Titanium dioxide and Carbon black:
Additional information: The listing applies to materials as "airborne, unbound particles of respirable size" and does not apply to materials that are within a product matrix.

100-41-4	ethylbenzene
1333-86-4	Carbon black
98-82-8	Cumol

· **Chemicals known to cause developmental toxicity:**
Additional information: Ethyl Alcohol is listed as “Ethyl Alcohol in alcoholic beverages” it is not listed any other way

64-17-5	ethanol

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
ethylbenzene
methyl methacrylate
butyl methacrylate

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 *Reviewed on 07/01/2026*

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 12)

· **Hazard statements**
Extremely flammable aerosol.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Water hazard class:** *Water hazard class 2 (Self-assessment): hazardous for water.*
· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

*
16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Reasons for alterations** *Update of GHS (EC) No. 1272/2008*
· **Relevant phrases** *Hazard warnings for the ingredients listed under point 3*

· **Department issuing SDS:** *department product safety*
· **Contact:**
· **Date of preparation / last revision** *07/01/2026 / 17*
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
OSHA: Occupational Safety & Health

(Contd. on page 14)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2026 Reviewed on 07/01/2026

Trade name: REVELL-SPRAY-COLOR
Different shades and gloss levels / metallic finishers

(Contd. of page 13)

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Aerosols 1: Aerosols – Category 1
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Sensitization - Skin 1: Skin sensitisation – Category 1
Carcinogenicity 2: Carcinogenicity – Category 2